SASSO SCALES
Weighing Solutions

PRECISION SCALES

JA-SERIS are ANALYTICAL weighing scales that are simple to operate,clean and maitain.**High precision of 0.001g diviosn.** They have a large bright LCD display comfortable for your readings and gives very stable readings to avaoid errors. JA series are doing well in the market for its ability to do internal calibration thus maintaining the accuracy of the machine.Also with them are serial port connectors for printer and computer connection for easier data management. **SUITABLE FOR LABORATORIES USERS**

Specifications:

Model	JA220	JA500	JA1000	
Capacity(kg)	220g	500g	1000g	
Division(g)	0.001g	0.001g	0.001g	
Display screen	LCD with back light			
Dimension(mm)	275X290X110			
Weighing units	g, t, lb,			
Weighing pan(mm)	Dial			
Housing structure	ABS plastic enclosure			
Calibration	External linear			
Power supply	AC 100~240V			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

GMC-SERIES are a high precision scales with a a big capacity of **up to 5000g and a precision of 0.01g**. With a bright LCD,Big pan.The scale will weigh those big lab capacity products that reuires a high precision with ease.Comes with a rechargable battery back up.External calibration with linear availability.**SUITABLE FOR LABORATORIES USERS**

Specifications:

Model	GMC-500	GMC-1000	GMC-2000	GMC-3000
Capacity(kg)	500g	1000g	2000g	3000g
Division(g)	0.001g	0.01g	0.01g	0.01g
Display screen	LCD with back light			
Dimension(mm)	275X290X110			
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Dial			
Housing structure	ABS enclosure			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

MOISTURE ANALYSER



MA-SERIES

Four languages menu (Spanish, Germany, English, Chinese)

▪ **HBM** Load cell Base.
▪5 inch touch panel.
▪40-180℃ test temperature
▪Built in RS232 for PC/printer or other equipment;
▪High Precision, fast measure, stable accuracy, simple opera

Specifications:

Model	DWP-3K	DWP-6K	DWP-15K	DWP-30K
Capacity(kg)	60g	6	15	30
Division(g)	0.001g	0.5	1	2
Display screen	LCD with back light			
Dimension(mm)	275X290X110			
Weighing units	*kg, g, t, lb, oz, pcs*			
Weighing pan(mm)	*275x 190(Stainless Steel, and 1.0mm in thickness)*			
Housing structure	Stainless steel IP67 rated			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

TABLE TOP SCALES

JWQ-JADEVER IS A HIGH PRECISION TABLE TOP SCALE THAT SHOWS THE ACTUAL WEIGHT OF A COMMODITY PLACED ON THE PAN,UNLIKE OTHER TABLE TOPS,IT HAS A LARGER PAN SIZE THAT MAKES IT COMFORATBLE TO WEIGH WIDER COMMODITIES. IT COMES WITH A RECHARGEBLE BATTERY AND CAN HANDLE HARSH CONDITIONS.SUITABLE FOR DRY INDUDTRIAL USES

Features;
Sample counting Digital Table Top Weighing scale
Accumulation, Accumulation Display and Accumulation clear functions
Resolution up to 1/15,000(free setting capacity and division)
Single point and linear calibration available
Hold function in peak, stable, or key operation
Lower / upper limit weighing alarming function
Zero range setting and filter setting for weighing under various condition
RS-232 interface for PC /Printer / U.KEY Connector / Blue Tooth(Optional)

Ideal for applications in production, packaging, warehouse, inventory, shipping and receiving areas

Specifications:

Model	JWQ-3K	JWQ-6K	JWQ-15K	JWQ-30K
Capacity(kg)	3	6	15	30
Division(g)	0.2	0.5	1	2
Display screen	LCD with back light			
Dimension(mm)	275X290X110			
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	275x 190(Stainless Steel, and 1.0mm in thickness)			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

DWP-WATERPROOF IS A HIGH PRECISION DURABLE TABLE TOP SCALE. IT CAN GIVE AN ACCURACY OF 0.5G ON A 15KGS CAPACITY. THAT BEING PREFERED BY MOST OF PACKAGING INDUSTRIES. IT IS ALSO A **WATERPROOF/DUST PROOF/MOISTURE PROOF IP67 APPROVED** WEIGHING SCALE THAT CAN HANDLE ANY WET ENVIROMENT AND MAINTAIN THE ITS HIGH PERFOMANCE. IT HAS A **STAILESS STEEL ENCLOSURE** AND RATED TO 1P67.COMES WITH A RECHAAREGEABLE BATTERY AND INTERNAL POWER SUPPLY. SUITABLE TO FOOD INDUSTRIES

Specifications:

Model	DWP-3K	DWP-6K	DWP-15K	DWP-30K
Capacity(kg)	3	6	15	30
Division(g)	0.2	0.5	1	2
Display screen	LED Red			
Dimension(mm)	275X290X110			
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	275x 190(Stainless Steel, and 1.0mm in thickness)			
Housing structure	Stainless steel IP67 rated			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

T-28 IS ASIMPLE AFFORDABLE TABLE TOP SCALE THAT SHOWS WEIGHT OF THE COMMODITIES PLACED ON THE PAN. COMES WITH A RECHARGEABLE BATTERY AND ITS WDELY USED IN INDUSTRIES FOR PACKAGING PURPOSES. SUITABLE IN A DRY CONDITION ENVIROMENT

Specifications:

Model	T28-3K	T28-6K	T28-15K	T28-30K
Capacity(kg)	3	6	15	30
Division(g)	0.2	0.5	1	2
Display screen	LCD with back light			
Dimension(mm)	275X290X110			
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	275x 190(Stainless Steel, and 1.0mm in thickness)			
Housing structure	ABS plastic housing			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

SASSO SCALES
Weighing Solutions

PLATFORM SCALES

LP7510-SERIES IS A HEAVY DUTY DURABLE WEIGHING MACHINE BUILT FOR VERY HARSH CONDITION. IT IS BUILT WITH STAINLESS STELL HOUSING FOR THE INDICATOR AND VERY STRONG MATERIALS FOR A LONG LASTING SOLUTION I WEIGHING. IT IS RATED 1P67 AND CAN HANDLE WET CONDITION PERFECTLY WITHOUT COMPROMISING THE PERFOMANCE. SUITABLE IN CHEMICAL,SALTY,WETY ENVIROMENT ETC. COMES WITH A RECHARGEABLE BATTERY AND AC-DC ADAPTOR FOR CHARGING

Specifications:

Model	LP7510-50K	LP7510-150K	LP7510-300K	LP7510-500K
Capacity(kg)	50kgs	150kgs	300kgs	500kgs
Division(g)	5g	10g	20g	50g
Display screen	LED Red			
Dimension(mm)	400*400mm	450*450mm	500*500mm	600*600mm
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Stainless steel			
LOAD CELL	Single point			
Housing structure	Stainless steel IP67 rated indicator			
Connectivity	RS232 for pc interface and printer			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

KW-SERIES IS PLATFORM IS WIDELY KNOWN YET BEING SIMPLE IT IS VERY DURABLE AND RELIABLE. ITS PERFOMANCE IS EXCELLENT. ABS INDICATOR ENCLOSURE AND HAS SERIAL PORT RS232 FOR CONNECTIVITY WITH PRINTER OR COMPUTER.HAS RECHARGEABLE BATTERY AND AC-DC ADAPTOR FOR CHARGING.

Specifications:

Model	KW-50K	KW-150K	KW-300K	KW-500K
Capacity(kg)	50kgs	150kgs	300kgs	500kgs
Division(g)	5g	10g	20g	50g
Display screen	LCD with back light			
Dimension(mm)	400*400mm	450*450mm	500*500mm	600*600mm
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Stainless steel or Checker plate			
Housing structure	ABS enclosure			
Connectivity	RS232 for pc interface and printer			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions



ID226-SERIES TECHNOLOGY OFFERS THE LATEST TECHNOLOGY IN WEIGHING SYSTEN WITH VARIETY OF CONNECTIVITY NOT ONNLY THE STANDARD RS232,IT HAS BOTH WIFI,BLUETOOTH, MODBUS-RTU. IT MAKES IT. WITH THIS IT IS ABLE TO WORK ON VERY HEAVY DATA COLLECTION ORGANISATION AS IT IS COMPATIBLE WITH VARIOUS CONTROL SYSTEMS. THAT MAKES IT STAND OUT FROM THE REST OF THE WEIGHING INDICATORS.IT HAS OPTIONS OF STAINLESS STEEL ENCLOSURE AND ABS FOR INDICATOR HOUSING

Specifications:

Model	ID226-50K	ID226-150K	ID226-300K	ID226-500K
Capacity(kg)	50kgs	150kgs	300kgs	500kgs
Division(g)	5g	10g	20g	50g
Display screen	LED Green or Red			
Dimension(mm)	400*400mm 450*450mm 500*500mm 600*600mm			
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Complete stainless steel pan/structure/load cells			
Housing structure	304 Stainless steel IP68 protected			
Connectivity	RS232/RS485 as standard, Option; Bluetooth, Wi-Fi, Modbus-RTU,TCP/IP, USB			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

RETAIL SCALES



CAS-CN1 network printing Scale provides total weighing solution to retail market. It is ideal for all retail outlets, grocery stores, delicatessen, restaurant, industrial and other general purpose applications.

Specifications:

Model	CNI-6K	CN1-15K	CN1-30K	
Capacity(kg)	6kgs	15kgs	30kgs	
Division(g)	1g	5g	5g	
Display screen	LCD with backlight			
ORIGIN	CAS is designed and manufactured by CAS in South Korea			
Weighing units	kg, g, lb.			
Price items	Per kg or Per unit			
Memory	10,000 PLU products			
Ingredients	1000 lists (up to 510 characters each			
Weighing pan(mm)	380*250mm Stainless steel			
Label widths	40-60mm			
Label lengths	30-290mm			
Housing structure	ABS enclosure			
Connectivity	RS232/RS485 as standard, Option; Wi-Fi, RJ45 interface			
Power supply	AC 100~240V			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

DIBAL D-500 NETWORKING

Specifications

Model	D500-6K	D500-15K	D500-30K	
Capacity(kg)	6kgs	15kgs	30kgs	
Division(g)	1g	5g	5g	
Display screen	LCD with backlight			
Interconnection	Up to 10 scales per section			
ORIGIN	D500 is designed and manufactured by DIBAL in Europe, Spain			
Weighing units	kg, g, lb.			
Price items	Per kg or Per unit			
Memory	10,000 PLU products			
PLU search	By code or Name			
Ingredients	1000 lists (up to 510 characters each			
Connectable devices	Pc/Barcode scanner/cash drawer/Queuing system(for hanging scales)/platform scale			
DWS web server	Allow access to information on each scale from any computer/mobile with internet			
Security	Access different protected menu via configurable passwords			
Weighing pan(mm)	380*250mm Stainless steel			
Label widths	40-60mm			
Label lengths	30-290mm			
Cassette	Removable cassette for easy roll replacement			
Vendors	Up to 20 vendors			
Housing structure	ABS enclosure			
Connectivity	RS232/RS485, TCP/IP ethernet as standard, Option; Wi-Fi, USB			
Power supply	AC 100~240V Rechargeable battery 6V X 4Ah			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

DIBAL D-900 NETWORKING

Model	D900-6K	D900-15K	D900-30K	
Capacity(kg)	6kgs	15kgs	30kgs	
Division(g)	1g	5g	5g	
Display screen	LCD touch screen-No need for pc			
Advertising	More dynamic and stylish buyers screen as a tool for advertising, more intuitive user menu,modern,compact and easy to clean, variety of formats			
Interconnection	Up to 16 scales per section			
ORIGIN	D900 is designed and manufactured by DIBAL in Europe, Spain			
Weighing units	kg, g, lb.			
Price items	Per kg or Per unit			
Memory	10,000 PLU products			
PLU search	By code or Name			
Ingredients	1000 lists (up to 510 characters each			
Connectable devices	Pc/Barcode scanner/cash drawer/Queuing system(for hanging scales)/platform scale			
DWS web server	Allow access to information on each scale from any computer/mobile with internet			
Security	Access different protected menu via configurable passwords			
Weighing pan(mm)	380*250mm Stainless steel			
Label widths	40-60mm			
Label lengths	30-290mm			
Printer	Linerless and autocutter			
Cassette	Removable cassette for easy roll replacement			
Vendors	Up to 20 vendors			
Housing structure	ABS enclosure			
Connectivity	RS232/RS485, TCP/IP Ethernet as standard, Option; Wi-Fi, USB			
Power supply	AC 100~240V Rechargeable battery 6V X 4Ah			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

FLOOR SCALES



ID226- SERIES platform weighing scale meets the needs of wet environment and washable compliant.

Specifications:

Model	PH226-500K	PH226-1000K	PH226-3000K	PH226-5000K
Capacity(kg)	500kgs	1000kgs	3000kgs	5000kgs
Division(g)	50g	200g	500g	1kg
Display screen	LED Green or Red			
Dimension(mm)	800*800mm	1m*1m	2m*2m	3m*3m
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Complete stainless steel pan/structure/load cells			
Housing structure	304 Stainless steel IP68 protected			
Connectivity	RS232/RS485 as standard, Option; Bluetooth, Wi-Fi, Modbus-RTU,TCP/IP, USB			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

SASSO SCALES
Weighing Solutions



LP7510-SERIES of Carbon-Steel Platform with Frame for dry environment

Features:

* Carbon-steel construction with frame.

* Powder-coated surface, anti-skidding design.

* Hermetically sealed steel weighing cells.

* Force transfer mechanism can be reset automatically.

* Accuracy weighing, easy installation.

* Low profile, well-formed shaped.

Specifications:

Model	Lp7510-500K	Lp7510-1000K	Lp7510-3000K	Lp7510-5000K
Capacity(kg)	500kgs	1000kgs	3000kgs	5000kgs
Division(g)	50g	200g	500g	1kg
Display screen	LED Red			
Dimension(mm)	800*800mm	1m*1m	2m*2m	3m*3m
Weighing units	kg, g, t, lb, oz, pcs			
Weighing pan(mm)	Heavy duty checker plate with carbon mild steel structure			
Housing structure	Stainless steel IP67 protected indicator			
Connectivity	RS232			
Power supply	AC 100~240V / rechargeable battery (6 V/ 4 AH)			

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

KW-SERIES heavy duty for all live animal weighing

Features:

* Weight capacity: 100kg~5000kg

* Platform size: 1.5m*1.5m~3m*5m

* Material: mild steel or stainless steel

* Main function: livestock weighing and animal weighing

* The fences can be assembled easily.

* Special weight capacity and scale size can be customized upon request.

* Suitable for weighing dogs, goats, pigs and cattle's.

Email Us

sales@sassoscales.co.ke
support@sassoscales.co.ke

Call Us Directly

+254 (0) 724 895 295
+254 (0) 704 868 152

www.sassoscales.co.ke

SASSO SCALES
Weighing Solutions

PROCESS CONTROL SOLUTIONS

ID510 Weighing Controller applied in Liquid Filling & Gas Filling solutions:

* 150,000 display division, CMC 6000e

* 200Hz ADC speed

* Green OLED dot matrix graph display

* RS232/485,100M LAN

* MODBUS-RTU, MODBUS-TCP are supported

* Multiple calibration modes: weight calibration, calibration free of weight, communication remote calibration

* Filling modes:

– Barrel positioning without lifting and auto control filling process

– Barrel positioning without lifting, external starts and controls filling

– Filling control with lifting, filling above liquid surface

– Filling control with lifting, filling under the liquid surface

* Screw capping control after filling

* 10 groups of recipe are supported

* Login via password menu management

* Computer software is supplied

* Options are supported,

– 8 inputs/12 OC output

SASSO SCALES
Weighing Solutions

ID511-WEIGHING SYSTEM

High Precision Spiral Powder Batching Solutions

* High precision batching control for powder

* Batching accuracy: 0.0005~0.001

Batching System

* Stock bin A: feed material A to weighing hopper A

* Weighing hopper A: weigh material A, control feeding and batching through Spiral feeder

* Stock bin B: feed material B to weighing hopper B

* Weighing hopper B: weigh material B, control feeding and batching through Spiral feeder

* Mixing machine: mix material A and material B after batching



Weighing Sampling Test System in Livestock Farming

Animal Feeding Process Control:

* Apply **ID511 weighing controller**

* Both PROFIBUS and Ethernet are available



weighing sampling test system in livestock farming

SASSO SCALES
Weighing Solutions

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

WEIGBDRIDGE SOLUTION



WINOX-BGE Fully Automated Unmanned Weighbridge

A TECHNOLOGY FROM LAUMAS

. **Specifications:**

Model	WINOX-BGE-40	WINOX-BGE-60	WINOX-BGE-80	WINOX-BGE-120
Capacity(kg)	40t	60t	80t	120t
Division(g)	5kg	5kg	7kg	20kg
Display screen	LCD with back light			
Application	Truck and Weighbridges management			
Dimension(mm)	3*9m	3*18m	3.5*22.5m	3.5*24m
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Laumas digital canister COD ,stainless steel, IP69k, Lightening protection(80,000A, Twist/angle protected,			
Indicator	WINOX-BGE, double(entry/exit) and single weighing as well as trailer weighing, up to 10,000 weighing records storage,52-key keypad and graphical display, load cell diagnostic display, up to 16 digital load cells, simultaneous management of 254 trucks			
Calibration	Theoretical calibration (via keypad) and real calibration with test weights			
Housing structure	304 Stainless steel enclosure IP68 rated			
Connectivity	RS232/RS485/Modbus-RTU/TCP/IP Ethernet, USB, Wi-Fi			
Power supply	AC 100~240V			

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

WINOX-BGED DIGITAL WEIGHBRIDGE (PIT OR SURFACE)

A TECHNOLOGY FROM LAUMAS

Designed with demanding industrial environments in mind, SASSO TRUCK SCALES weigh vehicles dependably and accurately over a long scale life.

Specifications:

Model	WINOX-BGE-40	WINOX-BGE-60	WINOX-BGE-80	WINOX-BGE-120
Capacity(kg)	40t	60t	80t	120t
Division(g)	5kg	5kg	7kg	20kg
Display screen	LCD with back light			
Application	Truck and Weighbridges management			
Dimension(mm)	3*9m	3*18m	3.5*22.5m	3.5*24m
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Laumas digital column canister COD ,stainless steel, IP69k, Lightening protection(80,000A, Anti-Rotation, up to 5 degree angle bend			
Indicator	WINOX-BGE, double(entry/exit) and single weighing as well as trailer weighing, up to 10,000 weighing records storage,52-key keypad and graphical display, load cell diagnostic display, up to 16 digital load cells, simultaneous management of 254 trucks			
Calibration	Theoretical calibration (via keypad) and real calibration with test weights			
Housing structure	304 Stainless steel enclosure IP68 rated			
Connectivity	RS232/RS485/Modbus-RTU/TCP/IP Ethernet, USB, Wi-Fi			
Power supply	AC 100~240V			

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

WB-PT PORTABLE/FOLDABLE WEIGHBRIDGE-SURFACE MOUNTED

A TECHNOLOGY FROM SASCO AFRICA

Specifications:

Model	WB-PT-80			
Capacity(kg)	80t			
Division(g)	16kg			
Display screen	LCD dot matrix display with back light			
Application	Truck and Weighbridges management			
Dimension(mm)	3*22.5m			
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	SASCO S24 Column canister, stainless steel IP69k rated, Lightening protection, Anti- twist, up to 5 degree angle bend			
Indicator	DD950 TOUCH SCREEN, double(entry/exit) and single weighing as well as trailer weighing, up to 10,000 weighing records storage,52-key keypad and graphical display, load cell diagnostic display, up to 16 digital load cells, simultaneous management of 254 trucks			
Calibration	Theoretical calibration (via keypad) and real calibration with test weights			
Housing structure	ABS enclosure IP6 rated, From BILANCIA Italy			
Connectivity	RS232/RS485/Modbus-RTU/TCP/IP Ethernet, USB, Wi-Fi			
Power supply	AC 100~240V			

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152



ID511 Is a high precision for process control solutions, Combined with the double shear beam load cells. It guarantees a smooth operations minimizing down time and loses at a very pocket friendly budget

Specifications:

Model	ID511-2000K	ID511-5000K	ID511-15000K	ID511-30000K
Capacity(kg)	2t	5t	15t	30t
Division(g)	500g	1kg	5kg	10kg
Display screen	LED Green			
Application	Process control, Liquid filling, Batch weighing, Dosing.			
Dimension(mm)	Tanks and Silos			
Origin	China			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Double Shear beam Zemic with full kit			
Indicator	ID511, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	Stainless steel enclosure			
Connectivity	RS232/RS485/Modbus-RTU/TCP/IP Ethernet, USB, Wi-Fi			
Power supply	AC 100~240V			

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

ID510 Is a robust hardy set for process control solutions, Combined with the HM9C load cells with kit. It guarantees longevity and reliability to handle any harsh condition and still give you outstanding performance

Specifications:

Model	ID510-5000K	ID510-15000K	ID510-30000K	ID510-100000K
Capacity(kg)	5t	15t	30t	100t
Division(g)	500g	1kg	5kg	10kg
Display screen	LED Green			
Application	Process control, Liquid filling, Batch weighing, Dosing.			
Dimension(mm)	Tanks and Silos			
Origin	China			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	HM9C with full kit			
Indicator	ID510, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	Stainless steel enclosure			
Connectivity	RS232/RS485/Modbus-RTU, Modbus-TCP, Profibus-DP, Ethernet			
Power supply	AC 100~240V			

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152



ID510 is a rail type control indicator with high precision and accuracy that is mainly suitable in dosing and packaging industries. Capable to interface to different make of PLC e.g. Siemens, Mitsubishi, Schneider

Specifications:

Model	ID551-2K	ID551-5K	ID551-15K	ID551-30K
Capacity(kg)	2t	5t	15t	30t
Division(g)	500g	1kg	5kg	10kg
Display screen	LED Red			
Application	Dosing and Packaging			
Dimension(mm)	Tanks and Silos			
Origin	China			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	T20 stainless steel			
Indicator	ID551, High precision, Din rail PC/ PLC Connectivity with rich communication interface			
Housing structure	Stainless steel enclosure			
Connectivity	RS232/RS485/Modbus-RTU/TCP/IP Ethernet, USB, Wi-Fi			
Power supply	AC 100~240V			

SASSO SCALES
Weighing Solutions

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

W200 is a high quality process control system from LAUMAS Italy. It offers reliable, accurate and stable readings. It comes with a complete control box. So operations are controlled on a single point avoiding multiple gadgets installation

Specifications:

Model	W200-5K	W200-15K	W200-30K	W200-100K
Capacity(kg)	5t	15t	30t	100t
Division(g)	500g	1kg	5kg	10kg
Display screen	LED Red			
Application	Process control, Liquid filling, Batch weighing, Dosing.			
Dimension(mm)	Tanks and Silos			
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Laumas HM9C,Alloy steel,IP67 rated with full kit, Intelligent junction box for load cells diagnosis			
Indicator	ID510, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	Stainless steel enclosure			
Connectivity	RS232/RS485/Modbus-RTU, Modbus-TCP, Profibus-DP, Ethernet			
Power supply	AC 100~240V			

SASSO SCALES
Weighing Solutions

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152



WINOX-G is a high quality process control system from LAUMAS Italy. It offers reliable, accurate and stable reading. It give graphic display to ease data reading and inline running's

Specifications:

Model	WINOX-G-5K	WINOX-G-15K	WINOX-G-30K	
Capacity(kg)	5t	15t	30t	
Division(g)	500g	1kg	5kg	
Display screen	LCD with back light,			
Application	Process control, Liquid filling, Batch weighing, Dosing.			
Dimension(mm)	Tanks and Silos			
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Analog Column canister, Stainless steel, IP68 rated, Intelligent junction box for load cells info			
Indicator	WINOX-G, Graphic display, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	Stainless steel enclosure			
Connectivity	RS232/RS485/Modbus-RTU, Modbus-TCP, Profibus-DP, Ethernet			
Power supply	AC 100~240V			

SASSO SCALES
Weighing Solutions

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

WINOX-G is a high quality process control system from LAUMAS Italy. It offers reliable, accurate and stable reading. It give graphic display to ease data reading and inline running's

Specifications:

Model	WDESK-G-5K	WDESK-G-15K	WDESK-G-30K	
Capacity(kg)	5t	15t	30t	
Division(g)	500g	1kg	5kg	
Display screen	LCD with back light,			
Application	Process control, Liquid filling, Batch weighing, Dosing.			
Dimension(mm)	Tanks and Silos			
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Laumas CBL low profile, stainless steel, IP69K rated, Intelligent junction box for load cell diagnosis			
Indicator	WDESK-G, Graphic display, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	ABS enclosure			
Connectivity	RS232/RS485/Modbus-RTU, Modbus-TCP, Profibus-DP, Ethernet			
Power supply	AC 100~240V			

SASSO SCALES
Weighing Solutions

www.sassoscales.co.ke

sales@sassoscales.co.ke

0724895295/0704868152

WINOX-2G is a high quality process control system from LAUMAS Italy. It offers reliable, accurate and stable reading. It give graphic display to ease data reading and inline visuals. Bigger LCD display for clear visibility

Specifications:

Model	WINOX-2G-5K	WINOX-2G-15K	WINOX-2G-30K	
Capacity(kg)	5t	15t	30t	
Division(g)	500g	1kg	5kg	
Display screen	LCD with back light,			
Application	Process control, Liquid filling, Dosing. For pharmaceuticals and food industries			
Dimension(mm)	Tanks and Silos			
Origin	Italy			
Weighing units	kg, g, t, lb, oz, pcs			
Load cell	Laumas FLC hygienic, stainless steel, IP69K rated, hygienic junction			
Indicator	WDESK-G, Graphic display, High precision, PC/ PLC Connectivity with rich communication interface			
Housing structure	ABS enclosure			
Connectivity	RS232/RS485/Modbus-RTU, Modbus-TCP, Profibus-DP, Ethernet			
Power supply	AC 100~240V			